SYRMATOTECHNICI - SCHINOTECHNIKI DIMITRIADIS DIMITRIOS



The company Dimitriadis Dimitrios was established in 2004, in Piraeus. The associations activities involve, both mercantile and technical operations Witch takes place in the marine and industrial area, all over Greece and abroad. Our qualifications:

- The knowledge of the traditional marine techniques (e.g. hand made slings.)
- The modern and sufficient equipment like hydraulic splicing press
- And the production of hand made accessories with ropes and wire ropes

FIRST IN GREECE WE MAKE FLAT BRAIDED SLING

(Tresse plate cable acier galva)





They are slings from wire ropes for heavy load and fragile cargos. For example coil steel, hot rolled, big rocks, marbles, vessel e.t.c

Our slings from wire ropes can lift cargos from 1 ton to 120 ton.

The flat braided sling can be used instead of chains slings, wire rope slings and webbing sling.

The difference is, that they have longer lifetime, they are more easy to use and they offer safety in their users.

Plus they are cheaper because you can buy only one instead of 50 wire ropes slings.

Our products are recognized today for their high quality worldwide.

We are proud because we give solutions with the best prices.

the products are accompanied with certificates

WIRE ROPES * SLING*CHAINS*ROPES*WEBBING SLING*RIGGING EQUIP*TESTING



	NUMBER OF STRANDS			
	8	10	12	16
DIAMETER			8	7 8
OF	WLL TONS			
STRAND			(<i>\(\)</i>
2mm			1	1.3
3mm			2.5	2.9
4mm	2,5	3	3,8	4,2
5mm	3,8	48	6	6,7
6mm	5,5	7,2	9	10
7mm	8	10	12,5	14
8mm	10	12,8	16	18
10mm	16	20	25	28
12mm	23	28	37	42
14mm		47	55	63
16mm			70	84



All products comply with the Essential Safety Requirements of Machinery Directives 2006/42/EC Manufacturing products are supplied with:

CE marking

EC certificate of conformity

on request, acceptance by an approved body.

we can construct spesial sizes on request. The max construction is from 20mm strand

All the constructions are from galvanized and stainless steel wire rope copmposition is $6x19\ 7x19\ 6x36$

^{*}safety factor 1:5